

DESCRIPTION

4Inch 360° 5CCT COB Round Gimbal Recessed Downlight With Integral Driver In Connection Box.

Directional lighted, tilted 30° , Rotation 360° , 38° beam and a precision lens.

Provides uniform brightness without scattering or glare.

Perfect choice for architectural styles such as living rooms, hallways, stairs and hallways.



FEATURES

- Aluminum die-cast body with adjustable gimbal
- Spring loaded retention arms allow for easy installation into ceilings with no need for a recessed hole
- TIR optic provides smooth, uniform light with a 38° beam angle
- Simple snap-in installation is fast and easy Tilting gimbal light source for directional lighting

INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

DIMMING

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

ELECTRICAL

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

SPECIFICATION

Model: 4EJCT12GRWH

Size: 4inchWattage: 12W

Lumens: 821lm/864lm/898lm/912lm/88lm

Voltage: 120V

Power Frequency: 60Hz

• Power Factor: >0.9

5CCT: 2700K/3000K/3500K/4000K/5000K

CRI: 90

Beam Angle: 38°Material: AL+PS

Lifespan: ≥50,000hours

Operating Temp: (-4°F~ 113°F) -20~45°C

· Dimmable: Triac Dimming

Rating: Suitable for Wet Locations

Warranty: 5 year limited

ENERGY SAVINGS

80% more energy savings than halogen lamps.

LISTING

ETL Listed.












Product View







30° Tilt Range




360° Rotation



Selectable CCT 2700K,3000K,3500K,4000K,5000K

DIMENSION



RECOMMENDED DIMMER

LUTRON				LEVITON	
TG-600PR-WH S-600PR-WH CTCL-153PDH-WH	TGCL-153PH-LA SLV-600P-AL DV-600PR-WH	SCL-153PH-WH GT-600P DVCL-153P	RNL06 MSCL-OP153M IPL06	6672 6674 DSL06	PD-6WCL MACL-153M//MA-R







Connector

Hole cutout card