

#### **DESCRIPTION**

Ultra slim design, lamp thickness only 0.49". Features color tunable technology lets the user choose between 2700K, 3000K, 3500K, 4000K, or 5000K. 3 levels of adjustable wattage. IC rated for direct contact with insulation.

Wet-location rated, ideal for bathrooms, laundry, porches and garage work rooms.

Available size: 4", 6"



#### **FEATURES**

- Edge-lit technology, with no glare or dark spots
- Continuous dimming from 100% to 10% with many Triac Dimmers
- Instant on
- No flicker

#### INSTALLATION

No existing recessed housing or junction box required.

Suitable for most new constructions.

Install J-Box in ceiling beam, and insert light right into drywall opening.

#### **DIMMING**

Compatible with most triac dimmers to give user a smooth 100%-10% dimming to choose the desired brightness.

## **ELECTRICAL**

This fixture is built with the highest quality 120V drivers, ensuring energy efficiency.

## **SPECIFICATION**

Model: 6EJCTSS05

Size: 6inch

Wattage: 9W-12W-15W

 Lumens:606Lm-807Lm-891Lm / 611Lm-812Lm-904Lm / 624Lm-833Lm-938Lm / 630Lm-840Lm-960Lm / 617Lm-824Lm-925Lm

Voltage: 120V

Power Frequency: 60Hz

Power Factor: >0.9

5CCT: 2700K/3000K/3500K/4000K/5000K

CRI: 90

Beam Angle: 120°Material: AL+PS

Lifespan: ≥50,000hours

Operating Temp: (-4°F~ 122°F) -20~40°C

Dimmable: Triac dimming

Rating: Suitable for Wet Locations

Warranty: 5 year limited

## **ENERGY SAVINGS**

80% more energy savings than halogen lamps.

## LISTING

ETL Listed.











# **Product View**



#### Selectable CCT & Selectable Wattage





# **DIMENSION**






SIZE	А	В	С	D	E	F
4inch	4.96"(126mm)	4.96"(126mm)	0.49"(12.45mm)	4.73"(120.1mm)	2.77"(70.4mm)	1.34"(34.1mm)
6inch	6.93"(176mm)	6.93"(176mm)	0.49"(12.45mm)	4.73"(120.1mm)	2.77"(70.4mm)	1.34"(34.1mm)

# **RECOMMENDED DIMMER**

	LUTF	LEVITON			
TG-600PR-WH S-600PR-WH CTCL-153PDH-WH	TGCL-153PH-LA SLV-600P-AL DV-600PR-WH	SCL-153PH-WH GT-600P DVCL-153P	RNL06 MSCL-OP153M IPL06	6672 6674 DSL06	PD-6WCL MACL-153M//MA-R

HOLE SIZE ACCESSORIES



SIZE	HOLE SIZE
4inch	4 21/64"(110mm)
6inch	6 19/64"(160mm)







Connector