

DESCRIPTION

This 5CCT 3Wattage Commercial Downlight is 15 in 1, available in 3 wattages and 5 CCT tunable. 120-277V input voltage, 0-10V dimming.

Wet-location and IC rated, ideal use for commercial complexes, hospitality, healthcare industry, schools, shopping centers, industrial areas and hotels.

Available size: 6", 8", 10"



FEATURES

- High luminous efficacy, up to 100LM/W
- High quality Aluminium shell with frosted PC diffuser
- Color removable trim available (sold separately): Brushed nickel, Black, Bronze

INSTALLATION

Easy fit installation, spring-action housing clips. Suitable for most new constructions.

DIMMING

Supports 0-10V dimming from 100% to 10%.

ELECTRICAL

This fixture is built with the highest quality drivers, ensuring energy efficiency.

SPECIFICATION

- Model: 8CMCT30LR05
- Size: 8inch
- Wattage: 17W-24W-30W
- Lumens: 1871Lm-2621Lm-3273Lm
- Voltage: 120-277V
- Power Frequency: 50/60Hz
- Power Factor: >0.9
- 5CCT: 2700K/3000K/3500K/4000K/5000K
- CRI: 90
- Beam Angle: 100°
- Material: AL+PC
- Lifespan: ≥50,000hours
- Operating Temp: (-4° F ~ 113° F) -20~45° C
- Dimmable: 0-10V dimming
- Rating: Suitable for Wet Locations
- Warranty: 5 year limited

ENERGY SAVINGS


80% more energy savings than halogen lamps.

LISTING



ETL Listed. FCC.Title24.



Product View



DIMENSION



Size	Hole Size
8Inch	8 5/64"(205mm)

RECOMMENDED DIMMER

LUTRON	LEGRAND
RMJS-8T-DV-B Diva DVSTV MS-Z101-WH DVSTV-WH	RH4FBL3PW

TRIM RING REPLACEMENT (SOLD SEPARATELY)



Brushed nickel



Black



Bronze

ACCESSORIES



Hole cutout card



Wire nuts